
Dwyer SERIES LPG5

2.5"LOW PRESSURE GAGE

3-2-3% Full-Scale Accuracy in a 2.5" Gage





The Series LPG5 2.5" Low Pressure Gage offers top of the line performance for pressure applications from 10 in w.c. to 10 psi. The LPG5 gages possess dual scales with 3-2-3% full-scale accuracy on a 2.5" dial. Units are made with a chrome plated steel housing and brass wetted parts. Units can withstand temperatures of -4 to 140°F (-20 to 60°C). This series is meant for the measurement of low pressures of gases and liquids and is ideal for air flow indication, liquid level and draft measurement. Series LPG5 gages are available with either a bottom or back connection option.

FEATURES/BENEFITS

- Chrome plated steel housing and brass wetted parts resist ambient for longer service life in harsh environments
- · Low pressure gage provides a selection to meet specific applications
- Specified with high ambient and process temperature ratings mean more robust uses and longer service-life
- Good accuracy gage for value-sensitive applications requiring more precise measurement and where vibration is a concern

APPLICATIONS

- · Air flow indication
- · Liquid level
- Draft measurement

USA: California Proposition 65

AWARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SPECIFICATIONS

Service: Compatible gases and liquids. Wetted Materials: Brass connection, bronze tube.

Housing: Chrome plated steel.
Lens: Polycarbonate.

Accuracy: ± 3-2-3% FS.

Pressure Limits: FS range.

Temperature Limits: -4 to 140°F (-20 to 60°C).

1-49/64

Size: 2.5" (63 mm).

Process Connections: 1/4" male NPT.

Weight: 8 oz (227 g).

MODEL CHART			
Model	Range in w.c. (kPa)	Model	Range psi (kPa)
LPG5-D8122N LPG5-D8222N	0 to 10 (0 to 2.5) 0 to 15 (0 to 3.75) 0 to 35 (0 to 8.75) 0 to 60 (0 to 15)	LPG5-D8822N LPG5-D9922N	0 to 5 (0 to 35)
Note: Change 22N to 42N for back connection option.			

OPTIONS	
Use order code:	Description
NISTCAL-PG1	NIST traceable calibration certificate