



Dwyer

SERIES TID

TEMPERATURE/PROCESS INDICATOR

Low Cost, 3-Digit Display, 1% Accuracy



The **Series TID Temperature/Process Indicator** displays temperature or a process value measured by a PTC or NTC thermistor or a 4-20 mA transmitter.

BENEFITS/FEATURES

- Thermistor or transmitter input models available
- 3 digit bright LED

APPLICATIONS

- Panel process indication
- Refrigerators, walk in coolers

MODEL CHART

Model	Input	Supply Power	Unit
TID-1110	PTC thermistor	115 VAC	°F
TID-1120	PTC thermistor	115 VAC	°C
TID-1410	PTC thermistor	24 VAC/DC	°F
TID-3100	4-20 mA	115 VAC	None
TID-3200	4-20 mA	230 VAC	None
TID-3400	4-20 mA	24 VAC/DC	None

SPECIFICATIONS

Range: -58 to 302°F (thermistor); -999 to 999 counts (4-20 mA).

Input: PTC/NTC thermistor or 4-20 mA.

Power Requirements: 115 VAC, 230 VAC, 24 VAC/DC.

Accuracy: > 1%.

Display: 3-digits; red, green or blue display.

Resolution: 1° or 0.1 count.

Front Panel Rating: IP64 (NEMA 3R).

Output: 5/12 VDC (model dependent).

Weight: 2.3 oz (65 g).

Compliance: CE, cURus.

ACCESSORIES

See page reference 1 below.