
MODEL 485B

THERMO-HYGROMETER

Measures % RH, Temperature, Dew Point and Wet Bulb





BENEFITS/FEATURES


- · Compatible with Dwyer AP1 thermo-anemometer and VP1 100 mm vane thermoanemometer probes (sold separately)
- Hold feature to freeze current readings on the display
- Stores up to 99 readings for future evaluation

APPLICATIONS

- Building commissioning
- Pulp and paper

MODEL CHART		
Model	Description	
485B-1	Digital thermo-hygrometer includes 9 V battery, sensing probe, wrist strap, hard carrying case and instructions	

OPTIONS	TIONS		
Use order code:	Description		
-NIST	NIST traceable calibration certificate		



SPECIFICATIONS

Service: Humidity, temperature, wet bulb and dew point temperature detection in clean air.

Temperature Limits: Process: -40 to 176°F (-40 to 80°C); Ambient: 5 to 125°F (-15

to 51°C).

Relative Humidity Range: 0 to 100% (non-condensing).

Relative Humidity Accuracy: ±2% FS over 10 to 90% @ 77°F (25°C).

Temperature Range: -20 to 140°F (-28 to 60°C).

Temperature Accuracy: ±0.9°F @ 77°F (±0.5°C @ 25°C).

Display: 4.5 digit LCD.

Resolution: 0.1%, 0.1°F/°C.

Probe Length: 8" (203 mm) insertion.

Power Requirements: 9 V alkaline battery, included, user replaceable.

Weight: 16 oz (454 g). Compliance: CE.

ACCESSORIE	S
Model	Description
A-47X-BOOT RP1	Protective magnetic rubber boot Thermo-hygrometer % RH and temperature probe with coiled cable